


TECHNICAL DATA SHEET

APPLICATION

Dayton Superior P34 Threaded Strap Anchor is used with P30 and P38 Corewall inserts to attach concrete wall panels to the structural frame.



WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.

FEATURES

- P34 Threaded Strap Anchor is used if a welded connection is required
- P34 is available with plain, electro galvanized, hot dip galvanized and stainless steel finishes
- Standard plate is 2.25" wide by 0.375" thick and comes in 6", 8", 10" or 12" length. Other sizes are available on special order

TECHNICAL DATA

Ultimate Tension = 26,700 lbs
 Ultimate Shear = 20,900 lbs

RELATED PRODUCTS

- P30 Corewall Inserts
- P38 Corewall Inserts

ORDERING INFORMATION

Product Code	Description	Weight
128564	CE 600 HOT DIPPED GALV.	1.7 LB
128565	CE 800 HOT DIPPED GALV.	2.3 LB
128566	CE 1000 HOT DIPPED GALV.	2.9 LB
128567	CE 1200 HOT DIPPED GALV.	3.55 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com