


TECHNICAL DATA SHEET

DESCRIPTION

The Dayton Superior P56PL Swift Lift Recess Plug is manufactured from high-grade elastomeric, thermal set urethane to provide improved tear, heat and chemical resistance.



FEATURES

- Versatile, reusable plug that utilizes a variety of accessories to provide installation and stripping ease in many different applications
- Available for 1, 2, 4 and 8-ton system sizes

INSTALLATION

1. Grasp the recess plug firmly across the top diameter of the plug
2. Application of pressure by the thumb and fingers on the outer edge of the plug will cause the plug to open up to allow insertion of the anchor
3. Swift Lift recess plugs provide two holes in the top surface that are used in the removal process - insert two screw drivers or steel rods into the holes and simply lever the two across the plug for easy removal

RELATED PRODUCTS

- P52 Swift Lift Anchors
- P66PL Tapped Plate
- P67PL Stud Plate
- P68PL Holding Plate

ORDERING INFORMATION

Product Code	Description	Weight
122152	1 TON SWL 2-1/2" DIA	0.116 LB
121045	2 TON SWL 3-1/4" DIA	0.274 LB
121046	4 TON SWL 4" DIA	0.476 LB
121047	8 TON SWL 5" DIA	0.912 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.