

# **TECHNICAL DATA SHEET**

#### DESCRIPTION

The PFB ReBoot Plastic Foundation Boot is a plastic, attachable boot used to position reinforcing steel. It consists of a gripping ring and structural base with a large bearing foot.

#### PRODUCT SPECIFICATION

■ Used below grade to provide proper concrete cover between rebar cage and earthen surface in drilled shaft construction as used in building, bridge, piers, retaining wall, sub-station and tower foundations. This product may also be used within caisson ring for the same purpose.



## **FEATURES**

- Up to 2000 lb compression rating
- Rigid rebar attachment
- One-size-fits-all product for use with #6 through #18 rebar
- Wide bearing foot
- I-beam construction base

#### **BENEFITS**

- No tools required, saves labor on the jobsite
- Saves money less parts needed due to strength of the PFB product
- Ensures reinforcement cages are properly positioned off base of drilled shaft

## **TECHNICAL DATA**

Product Code	Product Size	Bar Size	Compres sion Rating (lbs.)	Parts Per Carton	Weight
145201	3" cover	#6 and #7	1200	50	0.37 lbs.
145201	3" cover	#8 and #9	1500	50	0.37 lbs.
145201	3" cover	#10, #11, #14, and #18	2000	50	0.37 lbs.

## **RELATED PRODUCTS**

■ PFW - Bartender™

## ORDERING INFORMATION

REBOOT™ - N/A

Product Code	Description	Weight
145201	#6[19 MM] - #18[57MM]	0.371 LB

## **MANUFACTURER**

Dayton Superior Corporation 1125 Byers Road

Miamisburg, OH 45342

Customer Service: 888-977-9600 Technical Services: 877-266-7732 Website: www.daytonsuperior.com

## **WARRANTY (ACCESSORIES)**

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.

Page 1 of 1 File Date: 5/13/2024