

TECHNICAL DATA SHEET

DESCRIPTION

The Plastic On-Grade Chair is a high strength, individual, on-grade plastic rebar chair used to maintain the elevation of rebar or mesh in reinforced concrete. It consists of a one-piece molded plastic chair and is offered in a wide range of heights. The Plastic On-Grade Chair utilizes a base to provide stable support for a variety of applications. Each chair provides dual height positioning for greater flexibility on the job and reduced inventory needs.

APPLICATION

The Plastic On-Grade Chair can be used on all types of base surfaces. The integrated base design makes this support especially suitable for use on loose or soft surfaces, including: soil, gravel, carton forms, non-penetrable vapor barriers, insulation foam, etc. The chair can support a single upper mat of rebar or mesh.

PRODUCT SPECIFICATION

- Heights available from 1-1/2" to 3-1/2"
- Available in 1/2" increments
- Conforms to CRSI corrosion protection and performance guidelines



FEATURES

- Designed for optimal concrete flow and consolidation
- Dual height
- Secure top snap design to "lock" rebar in place

BENEFITS

- High strength plastic for maximum load capacity
- Non-corrosion materials
- No assembly required

RELATED PRODUCTS

- PCC AZTEC® CASTLE CHAIR

HOW TO ORDER

Specify (1) quantity (2) name (3) rebar cover height
 Example: 2000, Plastic On-Grade Chair, 3-1/2" & 4"

ORDERING INFORMATION

PLASTIC ON-GRADE CHAIR

Product Code	Description
GCCOMP-1.5-2	1-1/2" & 2"
GCCOMP-2-2.5	2" & 2-1/2"
GCCOMP-2.5-3	2-1/2" & 3"
GCCOMP-3-3.5	3" & 3-1/2"
GCCOMP-3.5-4	3-1/2" & 4"

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.