PSW - AZTEC® SPACE WHEEL™

REBAR SUPPORTS

TECHNICAL DATA SHEET

DESCRIPTION

Aztec Space Wheel – PSW is molded from composite plastic, providing high durability and strength across a large temperature range.

APPLICATION

The Aztec PSW is a side form spacer that clips easily over rebar, providing proper cover spacing between the formwork and rebar.

PRODUCT SPECIFICATION

- Available cover heights 3/8” to 3”
- Concrete cover is defined as the distance from where reinforcement sits in hub of wheel to outside of wheel where it contacts the form.



FEATURES

- Designed to fit a wide range of rebar and wire mesh sizes
- Minimal surface contact
- Standard “concrete Grey” color
- Lightweight

BENEFITS

- Quick and easy installation

APPROVALS / COMPLIANCE

- ACI 315-99
- CRSI RB4.1-2022 Compliant
- CRSI Load Category Non-Rated.
- May be used for all corrosion resistance classifications.

RELATED PRODUCTS

- PLW AZTEC E-Z Lok Wheel
- PFW BarTender Plastic Foundation Wheel
- REBoot Plastic Foundation Boot

ORDERING INFORMATION

Product Code	Description	Weight
121314	PSW - 3/8" Mesh	0.01 LB
121315	PSW - 1/2" Mesh	0.01 LB
121316	PSW - 3/4" Mesh to #3 [10MM]	0.01 LB
121317	PSW - 3/4"; #3 [10MM] to #4 [13MM]	0.02 LB
121318	PSW - 1" Mesh to #3 [10MM]	0.02 LB
121319	PSW - 1"; #3 [10MM] to #6 [19MM]	0.03 LB
121321	PSW - 1-1/4"; #3 [10MM] to #6 [19MM]	0.04 LB
121322	PSW - 1-1/2" Mesh to #3 [10MM]	0.04 LB
121323	PSW - 1-1/2"; #3 [10MM] to #6 [19MM]	0.04 LB
121324	PSW - 2" Mesh to #3 [10MM]	0.05 LB
121325	PSW - 2"; #3 [10MM] to #6 [19MM]	0.07 LB
121326	PSW - 2-1/2" Mesh to #3 [10MM]	0.07 LB
121327	PSW - 3" Mesh to #3 [10MM]	0.08 LB
121328	PSW - 3"; #3 [10MM] to #6 [19MM]	0.09 LB

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

File Date: 10/16/2026

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.