


PRODUCT DESCRIPTION

PVC 2-part rustication strips in widths from 2.25" to 11.5", all .75" x 45 degree in depth with base clip for attachment. PVC 0.5" x 60 degree rustications available in 2.0" and 3.0" widths with base clip for attachment. Both feature flexible edge seal, which reduces seepage of concrete under product.



APPLICATION

Rustications provide a variety of profiles designed by the architect for the panel reveals on the project.

FEATURES:

- Flexible Edge Seal—The Flexible Edge Seal fits tightly against the casting surface, preventing concrete seepage while creating sharp, crisp lines.
- Hidden Fastening System—No finish blemishes from screw heads or excess glue. With Victory Bear Snap Reveals or Base Clip Rustications, all screws and glue remnants are hidden under the surface for a sharp, glass-like finish.
- 100% PVC Reduces Tour Costs—PVC virtually eliminates concrete pitting caused by wood wicking. It also eliminates discoloration caused by wood sugars. It almost entirely eliminates the need for grinding and patching, saving you man-hours or subcontractor expense.

INSTALLATION

Step 1—Fasten the base clip to the casting surface with fasteners, tape or adhesive.

Step 2—Press one end of the rustication interlocking tooth grip into the end of the base clip.

Step 3—Press the entire length of the rustication into the base clip.

Step 4—Check to insure that the interlocking grips are fully engaged and the chamfer seal is pressed firmly against the casting surface.

Step 5 —Use Victory Bear 1' end pieces to finish rustication lines to finish chamfer.

(No form coat or bond breaker needed).

TECHNICAL DATA

- Material: PVC
- Length: 8'-0" each
- Coefficient of linear expansion: 0.0132 inches per degree F
- Weight: See chart
- Color: White or Grey Tone

PACKAGING AND PRODUCT CODES

Standard Profile (45°)								
Product Code	Part Name	Height "B"	Width "A"	Chamfer Angle	Pieces per Box	Weight lb/Box	LF per Box	Std. Length
128680	2.25 Rustication #743	.75"	2.25"	45°	18	25.1	144	8'-0"
128681	2.5 Rustication #712	.75"	2.50"	45°	12	18.0	96	8'-0"
128682	3.5 Rustication #713	.75"	3.50"	45°	20	45.0	160	8'-0"
128683	5.5 Rustication #714	.75"	5.50"	45°	14	46.0	112	8'-0"
128684	8.0 Rustication #747	.75"	8.00"	45°	8	44.1	64	8'-0"
128685	11.5 Rustication #711	.75"	11.50"	45°	6	47.9	48	8'-0"
Low Profile (60°)								
128702	2LP Rustication #729	.5"	2"	60°	22	26.4	176	8'-0"
128703	3LP Rustication #730	.5"	3"	60°	12	22.1	96	8'-0"
Base Clip								
128714	Base Clip #744				60	33.6	480	8'-0"

* Be sure to order 1' of base clip for each 1' of rustication.

HOW TO ORDER

Specify: (1) quantity, (2) Product Code, (3) name.

STORAGE

Materials should be stored out of direct sunlight to prevent long-term deterioration or color fading. Pieces can be stacked, but should be stored fully supported to keep them from warping.

WARRANTY

Dayton Superior warrants the product will be free from defects in material and workmanship. The foregoing warranty is in lieu of and excludes all other warranties not expressly set forth herein, whether express or implied by operation of law or otherwise, including but not limited to any implied warranties of merchantability or fitness.

Dayton Superior shall not be liable for incidental or consequential losses, damages or expenses directly or indirectly arising from the sale, handling or use of the product or from any other cause relating thereto. Seller's liability hereunder is expressly limited to replacement, in the form originally shipped, of goods not complying with this agreement or at Dayton Superior's election, a refund equal to the purchase price of the product.

Specifications and other information contained herein supersede all previously printed matter and are subject to change without notice.

TECHNICAL SERVICES

Dayton Superior's trained sales staff is available for consultation on all aspects of technical and design support, please call 888-977-9600.