

**TECHNICAL DATA SHEET**

**DESCRIPTION**

The WTW Premium Tie Wire is soft, annealed, small diameter wire designed to fit nearly every type of tie wire reel. It consists of clean, spooled wire formed around a square arbor for easy retraction.

**APPLICATION**

The WTW Premium Tie Wire is used to create a tie wire connection at rebar intersections.

**PRODUCT SPECIFICATION**

- 16.5 GA, 16 GA
- 3.5 LB Coils
- 50 KSI Tensile Strength
- Sold in quantities of 20 per box



**FEATURES**

- Soft, annealed composition
- Clean, smooth finish
- Square wound

**BENEFITS**

- Smooth fit in Tie Wire Reel
- Easy to retract at the end of the day
- Minimal reel cleaning from debris

**HOW TO SPECIFY**

Specific:  
 Rebar wire tie connections shall be made with WTW Premium Tie Wire as manufactured by Dayton Superior Corp.  
 Generic:  
 The rebar wire tie connection shall be made with wire complying with ASTM A510 as required by \_\_\_\_\_ (insert name here).

**APPROVALS / COMPLIANCE**

- ASTM A510

**RELATED PRODUCTS**

- PC110 Suprotek® Impalement Safety Cap
- PC200 Suprotek® Impalement Safety Cap

**HOW TO ORDER**

Specify: (1) quantity, (2) name, (3) gauge  
 Example: 20, WTW Premium Tie Wire, 15 Gauge

**ORDERING INFORMATION**

**PREMIUM TIE WIRE PLAIN (IMPORT) - N/A**

Product Code	Description	Weight
145384	16 GA	72.00 LB

**PREMIUM TIE WIRE PLAIN (IMPORT) PVC - COATED - N/A**

Product Code	Description	Weight
220275	16 GA PVD COATED	70.00 LB

**MANUFACTURER**

Dayton Superior Corporation  
 1125 Byers Road  
 Miamisburg, OH 45342  
 Customer Service: 888-977-9600  
 Technical Services: 877-266-7732  
 Website: www.daytonsuperior.com

**TECHNICAL DATA SHEET****WARRANTY (ACCESSORIES)**

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.